

Welcome to ALOGIC

Willkommen bei ALOGIC

Benvenuti a ALOGIC

Bienvenue à ALOGIC

Bienvenido a ALOGIC

ALOGICへようこそ

ALOGIC 에 오신것을 환영합니다

Quick Start Guide

# Quick Start Guide



## Introduction

The ALOGIC USB 3.0 to HDMI + DVI/VGA\* Multi Display Adapter makes it possible to convert any existing USB 3.0 port on a Laptop/Desktop into a HDMI + DVI/VGA\* output, with resolutions up to 2048x1152.

\*The adapters come included with a VGA converter (DVI to VGA converter), which allows conversion to a VGAoutput.

## Specifications

Model	U32HDDVVG
Input	USB-A 3.0
Output	HDMI Female x 1, DVI Female x 1, VGA Female x 1 (via included DVI to VGA Adapter)
Resolution	Up to 2048 x 1152
Physical Dimensions	123 (L) x 63 (W) x30 (H) mm
System Requirement	Windows 7/8/8.1/10 & Above and Mac OS Sierra & Above

## Features


- Add an extra Display or connect your Computer to a LCD TV or Projector through any available USB 3.0 Port on your Computer.
- Video streaming is supported up to 2048x1152.
- Supports both Extend and Mirror on to the extra display.
- Resumes from hibernation and suspend modes.
- Warranty: 1 Year

## Package Contents

- USB 3.0 to HDMI + DVI Multi-Display Adapter x 1
- CD (Driver & User's Manual) x 1
- USB Cable x 1
- Quick Installation Guide x 1
- DVI to VGA Adapter x 1

## Physical Layout

- 1 Power Port
- 2 USB 3.0 Connection Port
- 3 DVI Port
- 4 HDMI Port



## Installing the Driver

1. Insert the provided CD into your disc drive and the installer program will run automatically when the Driver CD is inserted. Then follow the on-screen prompts to complete the installation.  
For Windows® 7/ Windows® 8/ Windows® 8.1/ Windows® 10 users:  
A. Please click on Run Setup.exe to execute the installer program.  
B. Wait for the program to install the drivers.
2. Or please go to <http://www.displaylink.com/downloads> to download the appropriate driver from the website

## Making the Connection

Please connect the adapter to your monitor or computer after driver installation is completed.

NOTE: Please wait while DisplayLink software is configured for first use as below. Your screens may temporarily go black or flash during this process. Please click "OK" to start to use the adapter.

## Note

- Do not deliberately damage this product and put it in damp, direct sunlight or high temperature environment.
- If improper use, demolition or operation not according to the instructions result in any damage of your device or product, our company will not be liable for any compensation or maintenance responsibility.